### **TENDER FORMAT**

# TENDER FOR PURCHASE OF EQUIPMENTS FOR MIZORAM POLICE

1. NAME OF THE FIRM	<u>,                                      </u>
2. CORRESPONDENCE ADDRESS WITH TELEPHONE AND FAX NO	· · · · · · · · · · · · · · · · · · ·
3. LOCAL ADDRESS WITH TELEPHONE AND FAX NO.	·
4. WHETHER REGISTERED WITH NSIC / DGS&D IF YES ATTACH COPY	:
5. GST REGISTRATION & GST CLEARANCE CERTIFICATE	:
6. COPY OF AUTHORISED DISTRIBUTOR / DEALERSHIP/MANUFACTURER	· <u>·</u> ·
7. SPECIFICATIONS OF THE SYSTEM ALONGWITH LITERATURE/BROCHUR	E:
8. APPLICATION FEE	
9. EARNEST MONEY DETAIL	:
10. COPY OF TERMS AND CONDITION DULY SIGNED	:
GNATURE OF THE TENDERER VITH STAMP.	

### GOVERNMENT OF MIZORAM POLICE HEADQUARTERS : AIZAWL

\*\*\*

No.D.11014/CSS/Equipts/18-19/

Dated Aizawl thè

<sup>th</sup> November, 2019.

#### TENDER NOTICE

Sealed tenders are invited in two bid systems i.e. Technical Bid and Price / Commercial bid by the undersigned from the manufacturers, authorized distributors for purchase of following item(s) through registered post or these can be put personally in the sealed tender box kept in the Construction Branch of the office of the Director General of Police, Mizoram, Aizawl.

SI. No. Name o	fitems	Application fee	Earnest money
1. Equipments for Mizoram	Police at Annexure	₹ 1000/- (Non- refundable)	2 % of the value of the quoted items

### **TERMS & CONDITIONS**

The specifications of required items are enclosed with this notice. Tenderers are advised to quote their Rate after careful study of the tender specifications as well as the following terms and conditions:-

- 1. The tenders should reach the office of Director General of Police latest by 1200 hrs on 7.1.2020.
- Tender envelop(s) must be sealed and super scribed "TENDER FOR EQUIPMENTS FOR MIZORAM POLICE" which shall be addressed to Director General of Police, Mizoram.
- 3. Separate envelope should be used for TECHNICAL BID as well as for PRICE BID. The word "TECHNICAL BID / PRICE BID for purchase of Equipments for Mizoram Police due to open on 7.1.2020 at 2:00 PM" shall be prominently marked on the top of each envelope separately. Both these bids shall further be put in one envelope and sealed properly before putting in the tender Box duly super scribed. Tenderer (s) shall indicate complete specifications and all features of the items.
- 4. The Technical Bids will be opened first on 7.1.2020 at 2:00 PM and the PRICE BIDS will be opened only after scrutiny of technical bid and technical evaluation of the samples.
- 5. The item quoted with detail specification should be furnished in a separate sheet duly signed by the tenderer.
- 6. The tenderer can remain present himself or his authorize representative at the time of opening of tender.
- 7. A copy of terms and conditions duly signed by the tenderer, as a token of acceptance of the same should be attached alongwith the tender.
- 8. The tendering firm will also submit a certificate that the product offered by them is as per technical specifications of the tender.

- All the bidders whose technical bid is declared qualified by the Technical Committee will demonstrate their product before the Technical Evaluation Committee at a short notice.
- Only manufacturers, authorized distributors / authorized dealers can participate in the tender, the firm should submit proof of their manufacturing, authorized dealership / distributor. This is subject to verification if necessary.
- Only GST payee agencies are eligible to fill this tender. Interested agencies shall quote their GST Registration Number in their quotation and also attach documentary proof of having registered for the sale of such store/items etc. with the technical bid.
- Latest/current sales clearance certificate in English on the enclosed prescribed proforma must be attached with technical bid.
- 13. The application fee is non refundable.
- 14. In case the firm fails to attach the receipt / draft of application fee, the tender shall be rejected.
- Incomplete tender/conditional tenders will not be accepted.
- 16. All SSI units registered with NSIC/DGS&D for this item as per specification are exempted from the EMD. They have to enclose valid registration document/exemption certificate with their tender.
- 17. No tender will be accepted without requisite E.M.D. as mentioned in tender notice. The E.M.D. shall be in the shape of A/C Payee Demand Draft in favour of Director General of Police, Mizoram payable at Aizawl. The EMD can also be submitted either in the shape of FDR, Banker's cheque or Bank Guarantee. No interest will be given on E.M.D.
- 18. Tenderer would not be permitted to alter or modify their bids after expiry of the deadline for receipt of Bids.
- 19. The quoted price must be inclusive of all taxes and other charges etc. No claim for taxes/charges will be entertained at a later stage. Nothing over and above the quoted price would be payable to the successful bidder. Tenderer must quote the net price both in words as well as in figures. Any over writing/cutting etc. render the tender invalid.
- 20. The firm whose rates are accepted will have to deposit 5% of the total cost of the item as Performance Security in the shape of Bank Draft//Bank Guarantee FDR in favour of Director General of Police, Mizoram before the supply order is placed to the firm. In case, the firm does not complete the supply within the delivery period, liquidated damage charges will be charged @ 2% of total cost per month of the nem and action will be taken to blacklisting the firm and forfeiture of its Security money. No interest will be given on Security Money.

- 21. In case the firm fails to deposit the security money, the EMD of the firm will be forfeited.
- 22. The purchase committee, in order to satisfy itself can order on the spot enquiry to verify the soundness & capability of the item and any other information given by the tendering firms.
- 23. The rate's will be valid till supply of the item is completed, in all respect.
- 24. The rates will be F.O.R. at Aizawl 796001.
- 25. In case the firm fails to supply the item within stipulated delivery period, the item will be procured from the open market, if so desired by Purchase Committee and the difference of cost, if any, will be recovered from the Security Money and pending bills of the defaulting firm, by calling explanation after issuing notice.
- 26. The quantity of the items mentioned in the tender notice can be increased or decreased, at any stage till the delivery of consignment is completed.
- 27. Tenderer(s) shall indicate complete specifications and all features of the Equipment for Mizoram Police.
- 28. The payment will be made on receipt/acceptance of store in good condition as per prescribed specification. No advance payment will be made.
- 29. No claim for interest in case of delayed payment will be entertained by the Department.
- 30. The Purchase Committee reserves the right to relax any terms and condition in the govt. interest, with the approval of competent authority.
- 31. The purchase committee reserves the right to reject any tender or all tenders without assigning any reasons thereof.
- 32. All disputes are subject to the jurisdiction of the Courts in Aizawl.
- 33. Foreign Companies shall participate in the tender, only through their Distributors / Agent in India. No foreign company shall be entertained directly.
- In case of violation of any clause of contract/agreement deed, the explanation of the firm can be called by issuing show cause notice, if the reply is not found satisfactory. Security money can be forfeited as well as action for blacklisting can also be taken prior to taking any legal action.
- The tender will be rejected straight way without assigning any reasons if the firm involves in any criminal case, declared black listed by any Govt. / Semi govt. department/agencies etc.

- In case of any differences, the firm can be called for negotiation to patch up the differences on 36. table prior to approaching court.
- The bidder should carry a warranty/guarantee of subjected store for a period of at least one 37. year.
- The Price bid should be in accordance with the format as at Annexure-A. 38.

(C. LALNUNMAWIA) AIGP (P & L) for Director General of Police Mizoram, Aizawl.

No.D.11014/CSS/Equipts/18-19/19 P

Dated Aizawl the 22th November, 2019.

Copy to:-

1. The Director, I&PR for publication in the newspaper. Gist of the tender . enclosed herewith for publish in 2 (two) leading local newspaper at the size not more than 9 x 12 cms. for 2 consecutive days.

1n-Charge, Mizoram Police Website for information and necessary action.

Notice Board.

(C. LALNUNMAWIA') AIGP (P & L) for Director General of Police

Mizoram, Aizawl.

### NOTE:-

FULL ADDRESS : \_\_\_\_

	<u></u>				•
(A) THE	DOCUMENTS REQUIRED T FOLLOWING ORDER:-	O BE ATTA	CHED WIT	TH TECHNICA	L BID I
	TO SECURITION OF THE PARTY				
1.	E.M.D. in favour of Director	General of	Police, Mi	zoram, Aizawl	- 796001
2	amounting ₹/	75.00			
2. 3.	GST Registration Certificate.	/T: N: CV	·		
3. 4.	Latest GST Clearance Certificate Copy of authorized distributorship		AI.		
5.			NOIC :C-1-	: F1 (F)	•
6.	Certificate regarding registration Copy of terms and conditions	willi DUS&D,	NOIC II CIZ	im EMD exempl	1011.
0.	acceptance of terms and conditi	one signed	with seal	of the firm, in	token of
7.	The Demand draft of application		had with to	nder form	
8.	All Other supporting documents a	is required in the	he tender sh	all be attached	
	and a series of the series of	o required in a	no tonder on	an oc attached.	
(B)	<b>DOCUMENTS</b> REQUIRE	D TO	BE	ATTACHED	WITH
	COMMERCIAL/PRICE BID II				
			1 1 2		
	PRICE BID shall contain price	only and no	other doci	iments shall be	enclosed
	with the price bid.			-	•
4	5.4.05				
1.	Details of Rates, inclusive of all ta	axes including	freight inst	allation, commiss	ioning &
	testing of each items quoted by the	he tenderer sha	all be subm	itted on their lett	er Pad in
	clear terms, in words and in figure in the rates will not be entertained	es. The cutting	g & over-wr	iting not valid. T	he option
	in the rates will not be entertained		•		
	• 4.0				
	•				
		4.5			
			(		. )
					,
SIGN.	OF TENDERER	.1			
*					
NAME	E IN BLOCK LETTERS:				

## PROFORMA FOR PRICE SCHEDULE (Enclose with commercial bid)

### TENDER FOR PURCHASE OF EQUIPMENTS FOR MIZORAM POLICE

		Date of o	pening			Time		Hrs.
factor metho inspec	We	wintrol and test presentative	sentatives hich are fi ting of all of the pu	of M/s itted with a materials	modern eo	tured or use	nd where pro d by us are o ply the follo	open to
S. No.	Description of work/ item	Qty.	Unit Price In Indian Rupees	Extende d Price In Indian Rupees	Sales Tax/V AT In Indian Rupees	Other Govt. Levies, if any (To be specified)	Incidental charges, if any (To be specified)	Total Price FOR Destination In Indian Rupees
a	b	С	d	e	f	g	h	i
1.					•		•	
	,							
tende	nereby certified or document an s/items to be so	d are thorou	ighly awa	re of the n	ature of jo	ob required	to be done a	nd
We h	nereby offer to on(s) thereof as	carry out th s you specif	e job and y in the n	(or) suppl otification	y the good of award	ds/items deta	ailed above	or such
(Sign	nature and seal	of Bidder)						
Date			_				•	•

# GOVERNMENT OF MIZORAM POLICE HEADQUARTERS: AIZAWL

#### **SHORT TENDER NOTICE**

Sealed quotations are hereby invited for supply of Equipments for Mizoram Police from the bonafide manufacturers / authorized dealers. Tenders will be received upto 7,1,2020 at 1200 hrs and will be opened on the same day at 2:00 PM.

Details of the above items, terms and conditions can be had from the Office of the undersigned during office hours or Police Website <a href="www.police.mizoram.gov.in">www.police.mizoram.gov.in</a>

(C. LALNUNMAWIA) AIGP (P & L) for Director General of Police Mizoram, Aizawl

### **ANNEXURE**

## TECHNICAL SPECIFICATION OF EQUIPMENTS FOR MIZORAM POLICE

Sl. No.	Items	Technical Specification
1.0.	Security Equipments	
•		SIGNALLING: Display of use instruction PROAGRAMMABILITY: Chip card system for direct selection of the operating mode, according to International Security Standards or customer requirements. The use of the card may be protected by password ANALYSYS TIME: Very fast analysis time for a rapid flow-rate (2 seconds)
		MULTIPLE INSTALLATIONS: Automatic synchronization between 2 or more devices with a reciprocal distance of as a little as to 3 ft without the use of cables
		REMOTE CONTROL: Capacity for total remote control through an ₹-232C serial line
,		INSTALLATION AND MAINTENANCE: Automatic adjustment to environmental parameters with no need for initial or periodic calibrations. Proper environmental installation checked by means of a read-out of the general noise "GN" and electromagnetic noise "EN". Complete
		interchangeability of electronics units and antennae.
		DEGREE OF PROTECTION: IP 20 (IEC 60529), with a standard casing POWER SUPPLY: 115/230V'±15%, 50 ÷ 60 Hz, 30 VA
		COMMUNICATION CAPABILITY: ₹-232 serial interface, Ethernet network interface WORKING & STORAGE TEMPERATURE: -4°F to 158 °F / -35 °F to
1.	Shoe and leg scanner – 1 No.	158 °F RELATIVE HUMIDITY: 0-95% without condensation WEIGHT: Not more than 65kgs
		DIMENSIONS: 21.5" x 24" x 38" Approx
		ALARM MODES:
-		<ul> <li>Detection of metallic masses</li> <li>Sabotage or internal self-diagnosis</li> <li>TYPE OF SIGNALLING</li> </ul>
		• Visual: fixed or proportionate to the mass in transit – visible from 6m under lighting of 4000lux
		Audio: programmable up to 90 db(A) at 3 ft     CERTIFICATION AND CONFORMITY
		Certified as harmless to wearere of pacemakers, pregnant women and so forth
		<ul> <li>Harmless to magnetic media</li> <li>Confroms to the detection rerquirements of EU Reg. N°1862/2006 and N°185/2010</li> </ul>
		<ul> <li>N°1862/2006 and N°185/2010</li> <li>Conforms to the provisions of EU Reg N°857/2005 for Ajrport Security</li> </ul>
		<ul> <li>Conforms to the international standards currently applicable EC Regulations.</li> </ul>
1 1 1		Conforms to all Airport Security Standards worlwide

		Technical specifications:
		1. It should be capable of detecting all types of explosives of various
1	-	groups, including explosive items TATP (Tri-Acetone, Tri-Peroxide),
		HMTD (Hexa Methylene Tri-Acetone Diamine), Chlorates, Bromides
		ate, are and post-explosion.
		1 It should be spray type, packed in spray cans. However, reagents for
		detection of commonly available, IED compounds like TATP,
	A	HMTD Chlorates, and Bromides can be in liquid 19fm, 📝
	*	3. Should be able to detect 化 identify explosives at monograms level.
		4. It should have self adhesive collection papers to help detect trace
-	4 1	oxologives.
,	•	6 The capacity of each reagent should be good for at least 50 tests.
	-	6. The kit should have instruction chart and colour code display chart.
		7. The kit should be capable of showing instant reaction giving
	Explosive Detection &	immediate results.
2.	Identification Spray Kit - 5	8. The kit should be usable by normal field operative with minimal
6.1	Nos.	training.
	11001	9. The kit can be stored in field condition in a vehicle.
		10. The kit should have a shelf life of minimum 12 months at 100%
		potency,
1		Physical requirements
	, A	1. Should be easy earry and easy to use.
		2. Should be operable in all weather conditions and require no
		maintenance
		3. Should contain various types of sprays and collection papers in a
		pack.
		4. Should not pose any risk to technician/field officer and to the
		environment,
	1	5. Entire kit should be packed in a easy to carry plastic case, which
		should provide adequate protection to the kit.
		6. Weight of the kit should not exceed 650gms. POWER SUPPLY: 2x AA size alkaline or NiMH rechargeable batteries
	' · ·	CONTROL PANEL: Optical, acoustic and vibration alarm modes
		BATTERY LIFE: 100+ hours continuous service (AA alkaline batteries)
		Low battery indicator
		OPERATING TEMPERATURE: 40°F to 158°F
	Hand Held Metal Detector	STORAGE TEMPERATURE: 4°F to 176°F
3.	(HHMD) PD240C, CEIA -	RELATIVE HUMIDITY: 0 to 98% (without condensation)
	20 nos.	DIMENSIONS: 14.2" x 3.2" x 1.6" (approx)
		WEIGHT: Not more than 400g. (with battery)
		COMPLIANCE: Conforms to the NIJ, 0602.02 Standard and the NIJ
£ .		0602.03 Draft for metal detection, Conforms to the international standards
		currently applicable for safety, EMC and to the applicable CE regulations
and the same		de la companya de la

	*	
		TYPE: Single –Lens Reflex Digital Camera
	10 to	TENS MOUNT: F Mount with AF Contacts
١,		FEFFCTIVE ANGLE OF VIEW: DX Fromat, Focal Length equivalent to
		approx. 1.5x that of lenses with FX-format angle view
1		FEFECTIVE PIXELS: 24.2 Nillion
		IMAGE SENSOR: 23.5 X 15.6 mm CMOS Sensor
1		l morner privil C. 24.70 Million
		IMAGE SIZE (PIXELS): 6000 X 4000 (Large), 4496 x 3000 (Medium),
		L 2002 V 2000 (Small)
		LEUR FORMAT, NEE (RAW): 12 - OR 14 BIT, COMPRESED
		JPEG: JPEG – Baseline Compliant with fine (approx. 1:4), normal
		1 0) - hasia (approx 1:16) compression
		NEF (RAW) + JPEG: Single photograph recorded in both NEF (RAW)
- 1		and JPEG formats
	, ,	Promine CONTROL SVSTEM: Standard Neutral, VIVIQ
		Monochrome, Portrait, Landscape, Flat; selected Picturre Control can be
		1'C 1 -1 for ougtom Picture Controls
	,	MEDIA: SD (Secure Digital) and UHS-1 compliant SDHC and SDXC
		MEDIA: SD (Secure Digital) and Otto 1 company
. 4.	SLR Hitech Camera – Ino.	memory cards FILE SYSTEM: DCF 2.0 Exif 2.3, PictBridge
		VIEW FINDED. Eve-level pentamirror single-lens reliex viewinder •
		I DD A A COVED A CE, A norov US% horizoniai aliu 33/0 voiticui
		LAGACNIEICATION: Approx () 82x (50 mm I/1.4 lens at mining, 1.0m /
		EYEPOINT: 17mm (-1.0 m <sup>-1</sup> from center surface of viewfinder eyepiece
		lens) DIOPTER ADJUSTMENT: -1.7 to +0.5 m <sup>-1</sup>
		FOCUSING SCREN: Type B BriteView Clear Matte Mark VII Screen
-		REFLEX MIRROR: Quick Return
-		LENS APERTURE: Instant return, electronically controlled
	2	LENS AUTOFOCUS SUPPORT: Autofocus is available with AF-S, AF-
	7 to 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	P and AF-I lenses
		SHUTTER TYPE: Electronically controlled vertical-travel focal-plane
1-	•	
		shutter SHUTTER SPEED: 1/4000 to 30 s in steps of 1/3 or ½EV, Bulb, time
	***	SHUTTER FLASH SYNC SPEED: x=1/200s, Synchronizes wirh shutter
	* * * * * * * * * * * * * * * * * * * *	
'		at 1/200s or slower SELF TIMER: 2s, 5s, 10sw, 20s, /1 to 9 exposures
	4	SELF TIMER: 28, 38, 108W, 208, 71 to 7 exposures

	General Policing Equipments	Erone
	- B	Cleaning rod for 9mm Pistol
		Cleaning Rod for 7.62mm Rifle
-		Cleaner for Gas regulator
		Tool Combination MK-V GM
		Pull Through for 5.56mm Rifle
	•	Pull Through for 7.62mm Rifle
1.		Multi-utility tools:
		Needlenose Pliers
		Stranded-wire cutters
		Replaceable fuse-wire cutters
	A	Electrical crimper
5.	Armoury Tools	• Saw
	*	420HC Combo Knife     . *
		Replaceable Cutting Hook
		• Hammer
		Bolt Override Tool
		Replaceable C4 Punch
	10 m	8-32 Cleaning Rod/Brush Adapters
	•	Carabiner
		Large Bit Driver
= 1		3/8" Wrench and Front-sight Adjustment Accessory
_		Speaker:
		Portable
		USB/Bluetooth/SD Card connectivity
-		• Input Channels – 3 x Mic 0.65 mV/4.7 kW, 1 Tape, 1 x Keyboard 70
	Portable P.A. system for	mV/50 kW
. 6	0 0 4 D - 4-	• Frequency Response - 4 – 20,000Hz + 3dB
	42 nos.	AC Power consumption - 220 VA
		Microphone:
		Cordless FM Microphone
		Preferably Hi-Tune Bass PSX - 1200 DP

	Communication Equipments	1 6
	Communication Equipments	(a) Automated Synon Cipher System is secured means of communication for transmission of Confidential and Secret messages. With the introduction of this system the long procedure and time taken for encryption and decryption of Cipher messages using manual system will be replaced with speedy and accurate delivery of classified messages. Radio
. 7.	Automated Synon Cipher system with Data Terminal and accessories - 11 nos.	transmission is extremely vulnerable to interception communication security lapses cause serious threat to national security. To avoid interception and for speedy and accurate delivery of classified messages introduction of Automated Synon Cipher System is very important  (b) Specification of Data Terminal  Intel i3 Processor  Intel Chipset Motherboard  Intel HD Graphic/HD Audio/Wireeless - N  4GB DDR3 RAM  1 TB data HDD  18.5 TFT LED Display  DVD writer  Wifi-HDMI-USB card reader  Logitech USB Keyboard  Mouse  Logitech 2.1 Woofer
		<ul> <li>Canon LBP 2900 Laser Printer</li> <li>UPS 600VA (inbuilt battery)</li> </ul>

No.	in the state of th	Features Required
-	Personal Control of Co	• 4 wires transformer isolated audio interfaces with software
. 1		programmable input and output gain
	1	Sweet for single point to point and multi-site system
- 1		Network link control: Preferably enable or disable Network linking
		the DOTH CE Commend
- 1	•	- to the best possible audio quality AS I Div
		• The system should have the best possible date of Industrial Standards with minimal bandwidth consumption. The Industrial Standards with minimal bandwidth consumption.
		Bandwidth usage should be user configurable to optimize the Audio
		Quality Vs Bandwidth usage during the converse     Highly secured/Encrypted data communication to prevent interception
		<ul><li>(128 bit or better)</li><li>Support for unicast (point to point) and Multicast (Point to Multi-point)</li></ul>
		Support for unicast (point to point) and ividitions (2.3).
		communication.
		Automated call routing feature for allowing network user dial access to
-		multiple radios networks and conference can
		GOG MTT signal cupport
	P. C. O. ID (POID) - 5	LED indications at front panel for power.PTT,COS,Link
8_	Radio Over IP (ROIP) - 5	Multiple voice Codec
	nos.	G
-		Maximum Network Loading: 8-16 kbps typical (32 kbps Matte)
		Bit Rate: 6 bps – 256 kbps, user Programmatic
	<u>-</u>	No. of Radio channel support: 1
		Conferencing channel: 4
	•	Maximum number of Connectioning strangers     Power Input: 12V DC Typical (10.8V – 24V Max) @ 1.5A Max
	•	Connection
		Dode IICD
•	•	<ul> <li>Maintenance Port: USB</li> <li>Radio Connection: 4 wire transformers isolated audio interference with</li> </ul>
		PTT & Squelch
		News-to 10/100base - T Ethernet Port
		Vocoders: Any one of Opus/G.711/G.726 ADPCM/GSM (13kbps)
		Security: 128 Encryption or better
		• Form factor: Desktop
		Weight: Less than 500gms
		Operating temperature: 0°-55°C
		Humidity: 0-95% non condensing
		- numbers 0-7576 non condensing
	Medical Equipments	Standard Q Malaria PF/PV Ag Cassette X 40
		D M D 41 4 V02
9.	Malaria ICT 40 Test - 9 nos.	Buffer Bottle 4mX02     Manufacturer : SD Biosensor Healthcare Pvt. LTD
		Manufacturer: SD Biosellsor Heatingale 1 vt. BTB  Annual Company of the Diagnostical Company of the Diagnosti
		Manufacturer : Zephyr Biomedicals
	- 111 (C 4 b b) 25	25 X test devices
10.	Typhidot (Enterocheck) 25	1 X sample running buffer bottle
10.	Test - 9 nos.	25 X disposable sample applicators .
		1 X Package insert
-	•	Manufacturer : Loby Instrument Industry
5		Height : 3cm
	Sahli's Haemohlobinometer	• Length: 0.5cm
11.	with N/10 Hcl 500ml - 9 nos.	Hib pipette: 1000. 1 No.
1		Square H.b type: 2 no.

		Manufacturer: Mediclone Biotech Pvt. Ltd. Chennai
		• Widal Test: OH – 22X5ml
5		• For Semi Quantitative in=vitro detection of specific antibodies
12.	Widal test kit - 9 nos.	present in Berum against salmonella typhi O and H
	•	• Sensitivity: 5.0 mg/5ml
		• Packaging size : (2X5)ml
	•	• Store at 2°C-8°C
	Materials for PTS Thenza	
1	THE PROPERTY OF THE PROPERTY O	Mixer 8-Channel: 1 No
Ý.		• Sound Box 3-way 500w : 2 Nos.
		• Amp 1500w: 1 No.
		100 200 100 1 No
		<ul> <li>Monitor 12 200w. 1 No.</li> <li>Microphone: 2 Nos.</li> </ul>
	6 16 1 5 116 1 1	Dual 1 No
13.	Sound System Full Set – 1 set	Sound Cable Wire: 40 Meters
		Sound Cable Wite: 40 Meters: 3 Nos.     Microphone Cable 10 Meters: 3 Nos.
		<ul> <li>Microphone Cable 10 Meters: 2 Nos.</li> <li>Microphone Cable 5 Meters: 2 Nos.</li> </ul>
		Microphone Cable 5 Weters 7 2 1 vos.
-		Mic Stand: 1 No.     Stand: 2 Nos.
		• Speaker Stand: 2 Nos.
0		• Arc Current: 10A
	*	• Pulse Frequency: 50/60 Hz
		• Pilot Arc Current: 10A
		Rated Duty Cycle: 100%  ACM 1007  ACM 100
0.00		Motor type : AC Motor     AC Motor
77	*	• Voltage: 220V/380V
-14_	Gas Welding Machine - I no.	• Power(W): 3KW
124	Gas welding Machine 7 not	Max Gas output: 1000L/h     Second 12 MW
		Max Power Consumption : 3KW     A Second of Consumption : 3KW
		Max Working Pressure : 0.2Mpa
		Water feed : Automatic
		• Fuel: Pure Water, Electricity
li di		• Flame Temperature : 2800°
NO Media		• Warranty: 1 Year
19		Water Capacity: Not less than 9L
-		• Pressure: High
15.	Scuba Tank - 1 no.	Working Pressure: 300 Bar
13-	Scala Faire - Filo.	Burst Pressure : 450 Bar
		Material : Composite high performance carbon fiber
		Cylinder's Neck Thread: M18*1.5
		Design for use both at outdoor and indoor shooting ranges
		Programmable to perform various movement for firing practices
1		Portable and easy to operate
		Rugged all-weather system meeting IP 65 standards
	,	<ul> <li>Available both in wired and wireless configurations and operates either</li> </ul>
	•	with 230V AC Hz or with DC battery power.
-51	Electronic Target System	Realistic environment for specialized training
-16.	with Laptop - I no.	Reflex shooting of trainees
	-	Embedded motion sensors expose target automatically
		Firing Mode: Pop-Up, Slicing, Swing Out, Rotate
		Horizontal Sliding Targeys with varying speeds
		System should include Control Unit i.e. Laptop with LAN option for
		connectivity and preinstalled software for setting up of target
		movements, sensitivity of hit detection sensor and different exercises.
To a second second		

	Improvement of CPW	
17.	Impact Socket Set - 1 set	<ul> <li>½ Drive Hex Sockets</li> <li>½" 10 pes Set: 10, 11, 12, 13, 14, 15, 16, 17, 19, 21, 22 mm</li> </ul>
18.	8-Drawer Portable Workstation - 1 no.	<ul> <li>Dimension: 686 x 457 x 985mm</li> <li>Single operation locking system</li> <li>Heavy duty side handle</li> <li>Self locking ball bearing</li> <li>Drawer slide</li> <li>Double wall steel construction</li> <li>Castors feature 2 fixed 2 swivel with toe lock for safety and better mobility</li> <li>Average Drawer Load Capacity: 45 Kgs</li> <li>Trolley Load Capacity: 450 Kgs</li> </ul>
19.	Mechanic Tools Kit Box with 65 pieces of Tools - 1 no.	<ul> <li>½" Hex Socket 20 pcs: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32 mm</li> <li>Deep offset combination Spanners 18 pcs: 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 19, 20, 21, 22, 24 (mm)</li> <li>½" Ratchet Handle 1 pc</li> <li>½" Universal Joint 1 pc</li> <li>Hex key set with ball end-Long-Metric 7 pcs: 2, 3, 4, 5, 6, 8, 10(mm)</li> <li>½" Sliding T Bar 1 pc</li> <li>½" Spark Plug Socket 2 pcs: 16&amp;21(mm)</li> <li>Heavy Duty Pin Punch 1 pc: 6mm</li> <li>Locking Piller 1 pc: 250mm (10")</li> <li>Ball Pein Hammer-Hiclory Wood 1 pc: 456gms</li> <li>Phillips Screwdriver 4pcs: Ph 2x38mm, Ph 1x75mm, Ph 2x100mm, Ph 3x150mm</li> <li>Slotted Screwdriver 6 pcs: 6.5x3.8mm, 3x75mm, 4x100mm,</li> </ul>
20.	Hydraulic Two Post Lift - 1 no.	6.5x150mm, 8x150mm  Lifting capacity: 4 ton  Lift Height: 1700mm  Rise Time: 50 sec  Drop Time: 20 sec  Power Motor: 2.2 KW  Power Supply: 440v/220v  Width of the Rack: 3260mm  Height of the Rack: 2725mm  Width between Rack: 2728mm  Net Weight: 550 Kg/600 Kg

21.	Dent Puller Machine - 1 no.	<ul> <li>No. of Phases: 1 pg</li> <li>Secondary voltage: 7V/DC</li> <li>Control current connection socket: Renk XLR</li> <li>Connecting socket diameter: 13mm</li> <li>Product weight(per item): 25 Kg</li> <li>Secondary current short circuit: 1800 A/AC</li> <li>Length: 330mm</li> <li>Width: 210mm</li> <li>Height: 300mm</li> <li>Cable cross section: 4 mm²</li> <li>Nominal Voltage: 230 V/AC</li> <li>Frequency: 50 Hz</li> <li>Power rating: 2 kw</li> <li>Main fuse: 16 Amp</li> </ul>
22.	Heavy Duty Transmission Hydraulic Jack - 1 no.	<ul> <li>Secondary current short eircuit: 1800 A/AC</li> <li>Capacity: 1~10 tons</li> <li>Min. Height: 850mm</li> </ul>
23.	Heavy Duty Car Washer - 1	<ul> <li>Max Pressure: 160 bar</li> <li>Rated input power: 4000W</li> <li>Operating pressure: 150 bar</li> <li>Max inlet temperature: 50°C</li> <li>Cable Length: 5 m</li> <li>Hose length: 15 m</li> <li>Material (Hose): Rubber with steel jack</li> <li>Weight (without accessories): 40.6 kg</li> <li>Max flow rate: 800 l/h</li> <li>Pump system: Wobble plate</li> <li>Pistons: Ceramic conted</li> <li>Motor type: Induction</li> <li>Lance: Variably adjustable fan spray lance (stainless steel)</li> <li>Three-phase current: 400 V, 3 Phase</li> </ul>
24.	6 inch Sander Machine - 1 no.	Features  Grinding speed, shorten operating time  Uniform and Smooth polishing effect.  Anti-freeze slip pouches, suitable for prolonged use  Light weight, low height, easy to operate  Suitable for automotive sheet metal coating operations  Technical specifications  Free speed: 9000RPM  Max Pressure: 90PSI  Sanding pad: 6"/125mm  Air inlet: ¼ NPT  Air hose: 3/8"  Average air consumption: 12 CFM (340 1/min)  Package included: 1 Set x Air Palm Sander